

## Robust and comfortable - for tying stalls and elevated feed stalls

In tying stalls and elevated feed stalls, robustness and comfort are two main challenges. The KEN mat is ideal for this application area, as it is particularly form stable and durable. Moreover, the simple stud profile on the lower side ensures softness. KEN is available as a single mat with a straight edge and as a puzzle cut option in a wide range of dimensions.

**Incidentally:** Elevated feed stalls also help to reduce ammonia emissions!



- Proven, low maintenance pebbled surface
- Wide range of dimensions
- Longitudinal and cross installation



## Technical data

Dimensions (mm / cm)	Thickness	Width	Length
<b>KEN (straight edge)</b>	2 cm	90 cm	130 / 140 / 150 / 165 cm
		100 cm	130 / 140 / 150 / 165 / 175 / 185 / 200 / 220 / 350 cm
		110 cm	140 / 150 / 165 / 175 / 185 / 200 / 220 / 350 cm
		120 cm	150 / 165 / 170 / 175 / 180 / 185 / 200 / 220 / 350 cm

Dimensions (mm / cm)	Thickness	Width	Length
		130 cm	150 / 165 / 175 / 185 / 200 / 220 / 350 cm
<b>KEN Puzzle</b>	2 cm	105 cm	140 / 150 / 165 / 175 / 185 cm
		115 cm	140 / 150 / 165 / 175 / 185 / 200 cm
		125 cm	150 / 165 / 175 / 185 / 200 cm

Dimensions (in / ft)	Thickness	Width	Length
<b>KEN (straight edge)</b>	$\frac{3}{4}$ "	35 $\frac{1}{2}$ "	51 $\frac{1}{4}$ / 55 $\frac{1}{8}$ / 59 / 65"
		39 $\frac{3}{8}$ "	51 $\frac{1}{4}$ / 55 $\frac{1}{8}$ / 59 / 65 / 68 $\frac{7}{8}$ / 72 $\frac{7}{8}$ / 78 $\frac{3}{4}$ / 86 $\frac{5}{8}$ / 137 $\frac{3}{4}$ "
		43 $\frac{1}{4}$ "	55 $\frac{1}{8}$ / 59 / 65 / 68 $\frac{7}{8}$ / 72 $\frac{7}{8}$ / 78 $\frac{3}{4}$ / 86 $\frac{5}{8}$ / 137 $\frac{3}{4}$ "
		47 $\frac{1}{4}$ "	59 / 65 / 67 / 68 $\frac{7}{8}$ / 71 / 72 $\frac{7}{8}$ / 78 $\frac{3}{4}$ / 86 $\frac{5}{8}$ / 137 $\frac{3}{4}$ "
		51 $\frac{1}{4}$ "	59 / 65 / 68 $\frac{7}{8}$ / 72 $\frac{7}{8}$ / 78 $\frac{3}{4}$ / 86 $\frac{5}{8}$ / 137 $\frac{3}{4}$ "
<b>KEN Puzzle</b>	$\frac{3}{4}$ "	41 $\frac{3}{8}$ "	55 $\frac{1}{8}$ / 59 / 65 / 68 $\frac{7}{8}$ / 72 $\frac{7}{8}$ "
		45 $\frac{1}{4}$ "	55 $\frac{1}{8}$ / 59 / 65 / 68 $\frac{7}{8}$ / 72 $\frac{7}{8}$ / 78 $\frac{3}{4}$ "
		49 $\frac{1}{4}$ "	59 / 65 / 68 $\frac{7}{8}$ / 72 $\frac{7}{8}$ / 78 $\frac{3}{4}$ "

## Installation and fixing

### Fixing at the head edge

[Installation instructions](#)

## Maintenance tip

**When used as lying mats, add a thin layer of bedding**, e.g. soft milled straw or mineral materials (moisture in the lying area can cause various conditions, including skin diseases and infections)

**Keep mat as clean as possible in an elevated feed stall** Essential for hoof health and slip resistance!

**Treatment with a high-pressure cleaner and standard cleaning agents possible.**

### KRAIBURG warranty

10 years

Detailed information on our warranty (with consideration of the service life) is available upon request from your contractual partner / dealer.

### Tolerances

Thickness: +3/-2 mm

Width + length: +/- 1.5% (DIN ISO 3302-1 tolerance class M4)

Please refer to the relevant KRAIBURG specifications and installation instructions, which provide valuable hints and tips.

*The products featured here are exclusively intended for the demonstrated applications. Technical details subject to change. Our General Terms and Conditions apply. Legal basis is the German version of the document.*

**Note on imperial measurements:** Our products are manufactured according to metric specifications. The imperial measurements are therefore only intended as a guide. Inaccuracies may occur due to conversion and rounding.